

Specifications

SMART Board® interactive whiteboard system

Model SB885ix2


Overview

Your SMART Board 800ix2 interactive whiteboard system combines the use of a SMART Board 885 interactive whiteboard, a SMART UX80 projector, and other accessories and optional equipment.


It uses the WXGA (16:10) ultra-short-throw, high-offset SMART UX80 projector and delivers high definition, high performance interactivity that is virtually shadow-free and glare-free. You can do everything you can do at your computer—open and close applications, meet with others, create new documents or edit existing ones, visit websites, play and manipulate video clips and more— just by touching the interactive surface. Four users can draw on the interactive surface at the same time, and you can use an array of gestures within applications.

The projector supports video and audio connections from a variety of devices including DVD and Blu-ray™ players, document cameras, and other high-definition sources, and can project media from these sources onto the interactive screen. All HDMI 1.4 inputs are HDCP compliant.

See smarttech.com for more information on this product.



Dimensions and weights*



SMART Board 885ix2 interactive whiteboard

Weight

55 lb. (25 kg)

Shipping dimensions

4 3/8" W × 56 3/4" H × 88" D
(11.1 cm × 144.1 cm × 223.5 cm)

Shipping weight SB885ix2

68.3 lb. (31kg)

Accessory Kit (includes pen tray)

Weight

12 lb (5.5 kg)

Shipping dimensions

40 1/8" W × 7" H × 3 7/8" D
(102 cm × 17.7 cm × 9.8 cm)

SMART UX80 projector

Weight (projector only)

19 lb 6 oz. (8.8 kg)

Weight (projector + boom)

33 lb 12 oz. (15.3 kg)

Shipping weight (projector + boom)

42 lb 5 oz. (19.2 kg)

Shipping dimensions

25 5/8" W × 23 5/8" H × 15 3/4" D
(65 cm × 60 cm × 40 cm)

Remote control dimensions

1 5/8" W × 3 3/8" H × 1/4" D
(4.1 cm × 8.6 cm × 0.6 cm)

Extended control panel (ECP) - SB885ix2 only

Dimensions

6 5/8" W × 2 18/" H × 4 5/8" D
(16.8 cm × 5.5 cm × 11.9 cm)

Weight

5 lb. 11 oz. (2.6 kg)

Shipping dimensions

16 1/2" W × 14" H × 3" D
(41.9 cm × 35.6 cm × 7.6 cm)

*All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg)

Hardware

Projector

Brightness (standard)	3600 lumens (typical) in Standard 280 W mode at a CCT of 6500 K by the IEC method
Brightness (economy)	2880 lumens (typical) in Economy 230 W mode at a CCT of 6500 K by the IEC method
Native resolution	WXGA 1280 × 800
Aspect ratio	Native 16:10 aspect ratio with support for 16:9, and 5:4 and 4:3 aspect ratios with source image scaling
Throw ratio	Ultra-short throw, 0.18:1 ratio
Throw distance	14 3/4" (37.5 cm)
Display technology	Single chip DLP® technology by Texas Instruments™
Lamp life	2500 hours in Standard 280 W mode, 3000 hours in Economy 230 W mode
Integrated speaker	10 W mono
Projector noise	36 dBA (high fan speed) or 33 dBA (standard fan speed), measured using the JIS method
Contrast ratio (typical)	2000:1
Video system compatibility	HDTV (720p and 1080p) video system compatibility and HD Ready (HDMI technology and 720p) available, NTSC, NTSC 4.43, PAL, PAL-N, PAL-M, SDTV (480i/p and 576i/p)
Video interface compatibility	HDMI 1.4 (×2) and VGA (RGB or Component)
Horizontal frequency	31 kHz–68 kHz
Vertical frequency	30 Hz–85 Hz
Clock frequency	25 MHz–150 MHz
External management	IR Remote, RS232 control port, internal web page, Crestron RoomView® management via Ethernet



Interactive whiteboard

Touch resolution	4000 × 4000
Digitizing technology	Four-camera DViT® (Digital Vision Touch) technology with steel coated dry erase surface
Accessories	Two ergonomic pens with comfort grip and rectangular eraser

Extended Control Panel (ECP) SB885ix2 - included with the system, not pre-attached to the pen tray

SPECIFICATIONS

SMART BOARD INTERACTIVE WHITEBOARD SYSTEM – MODEL SB885IX2


Included cables and hardware	For SB885ix2 14' 9" (4.5 m) power cable Infrared remote control 16' 5" (5 m) USB cable 13' 5 1/2" (4.1 m) 3.5 mm stereo audio cable Projector wiring harness Notebook/laptop harness
-------------------------------------	---

Theft protection	Projector system padlock ring SB800 system - Kensington security slot
-------------------------	--

Connectors

Projector connectors	3.5 mm phone jack audio input 3.5 mm phone jack audio output DB15F RGB VGA video input DB9F RS-232 control port HDMI 1.4 input (x2) Power (100V–240V AC at 50 Hz–60 Hz) USB-B port - for service use only RJ45 - ethernet connector RJ45 - second projector control 7-pin mini-DIN for ECP data 4-pin power-DIN 5V/2A output connector for ECP USB HUB/switch power
-----------------------------	---

ECP connectors	RJ11 6-wire internal pen tray connection 11-pin connects to projector wiring harness 4-pin room control system via SB8-CTRL adapter cable USB Type B connects to bottom of pen tray USB mini-Type B (x2) primary and secondary computer connections USB Type A for USB Drive or memory stick
-----------------------	---

 **IMPORTANT**
The USB Type A connects only to the Primary computer

Computer requirements

SB885ix2	Windows® operating system or Mac operating system software and SMART Notebook software installed
-----------------	--

Storage and operating requirements

Power requirements	100V–240V AC at 50 Hz–60 Hz
---------------------------	-----------------------------

Power consumption

Full mode	375 W
Standard mode	311 W
Standby mode	0.5 W

Operating temperature

Interactive whiteboard	41°F to 95°F (5°C to 35°C) from 0' to 6000' (0 m to 1800 m) 41°F to 86°F (5°C to 30°C) from 6000' to 9800' (1800 m to 3000 m)
------------------------	--

Projector	Standard speed: 0' to 6000' (0 m to 1800 m): 41°F to 95°F (5°C to 35°C) High speed: 6000' to 6800' (1800 m to 2100 m): 41°F to 86°F (5°C to 30°C)
-----------	--

Storage temperature	-4°F to 122°F (-20°C to 50°C)
----------------------------	-------------------------------

Humidity	5% to 95% storage relative humidity, non-condensing 5% to 85% operating relative humidity, non-condensing
-----------------	--

Certification and compliance

Regulatory certification	CB, CCC, CE, C-Tick, FCC, KC, GOST-R, NOM, PSB, PSE, TUV-GS, UL/CSA(US/Canada) and VCCI
---------------------------------	---

Environmental compliance

China	EIP
European Union	REACH, RoHS, WEEE, Battery, Packaging and ErP Standby
U.S.	Packaging and Conflict Minerals

Warranty

Interactive whiteboard	Two-year limited equipment warranty OR Five-year limited equipment warranty upon registration
Projector	Three-year limited equipment warranty
Projector lamp	1000-hour/one-year warranty
ECP	Three-year limited equipment warranty

Purchasing information**Order numbers**

SB885ix2	87" (221 cm) diagonal SMART Board interactive whiteboard with a SMART UX80 projector system. Includes a SMART Notebook software installation DVD.
1018740	Replacement SMART UX80 projector lamp module
1013576	Projector hardware kit smarttech.com/kb/160505

Optional extended warranty

EWY2-UX80	UX80 projector extended warranty (available at time of projector purchase only)
-----------	--

Optional accessories	See smarttech.com/accessories
-----------------------------	--

SMART BOARD INTERACTIVE WHITEBOARD SYSTEM – MODEL SB8851X2

smarttech.com/support

smarttech.com/contactsupport

© 2015 SMART Technologies ULC. All rights reserved. SMART Board, DVIT, SMART Meeting Pro, SMART Notebook, SMART GoWire, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. RoomView and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof covered by one or more of the following U.S. patents. www.smarttech.com/patents. Contents are subject to change without notice. 09/2014.